

# B809

## DISCREET HIGH- PERFORMANCE

PRESCRIPTION  
FRAME  
★ EXCELLENCE



PXFB8091022



B809BL



B809BXL

23 g - size S  
31 g - size L  
33 g - size XL



### SUPPLIED WITH

Hard case,  
microfibre cloth



### FRAME

• TR90/Metal/Nylon

### LENS MATERIAL AVAILABLE

• CR39  
• Polycarbonate  
• Trivex

- + BUILT-IN SIDE SHIELDS
- + ADJUSTABLE REINFORCED TEMPLES
- + NOSE BRIDGE WITH NON-SLIP PADS (L AND XL)
- + RIVETED SIDE SHIELDS
- + 3 SIZES: S, L AND XL

**bolle**  
SAFETY

# B809

## DISCREET HIGH- PERFORMANCE

MODEL	REFERENCES	SIZE	FRAME MARKING	TEMPLE LENGTH	
<b>B809</b>	S - ■ Black	PXFB8091022	52/17	EN166 F CE	130 mm
	L - ■ Black	B809BL	54/17	EN166 F CE	127 mm
	XL - ■ Black	B809BXL	57/17	EN166 F CE	130 mm

### LENS MARKING

#### Polycarbonate lens:

**F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.

#### CR39 lens:

**S.** Extra strong, resists a 22 mm 43 g ball falling 1.30 m at 5,1 m/s.

#### Trivex lens:

**F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.

### STANDARD ASSEMBLY RESTRICTIONS:

**Maximum sphere power:** +10/-10

**Maximum cylinder compared with sphere :** +/-6.


### CORRECTED BASE:

**Corrected base :** 4

### FRAME MARKING

**EN 166 :** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

**F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.

CE European standard  Manufacturer name

**Bollé safety product approval certificates to CE standards will be sent on request.**

### CLEANING AND STORAGE

**CLEANING :** The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE :** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE :** All products must be stored in a dry and clean environment.

### PACKAGING AND EAN13 CODE

	PXFB8091022	B809BL	B809BXL
Per piece	3660740010041	3660740009106	3660740008376

### CHARACTERISTICS

LENS MATERIALS	CR39, Polycarbonate, Trivex
TYPES OF CORRECTIONS AVAILABLE	Single vision - Bifocal - Progressive - Degressive
FRAME MATERIALS	TR90/Metal/Nylon



01/04/2020

Europe Bollé Safety  
34 rue de la Soie  
69100 Villeurbanne - France  
Tél. : 00 33 (0) 4 78 85 23 64  
Fax : 00 33 (0) 4 78 85 28 56  
contact@bolle-safety.com

[bolle-safety.com](http://bolle-safety.com)

U.K. Bollé Safety  
Unit C83 - Barwell Business Park Leatherhead Road - Chessington  
Surrey - KT9 2NY  
Tél. : 00 44 (0)208 391 4700  
Fax : 00 44 (0)208 391 4733  
e-mail : [uk@bollebrands.com](mailto:uk@bollebrands.com)

**bolle**  
SAFETY