

WHE00108

EN



TECHNICAL DETAILS



MATERIAL
EXTERNAL SHELL:
HD Polypropylene
INTERNAL SHELL:
HD Expanded Polystyrene
HEADBAND:
Soft PA Nylon



STANDARD
EN 12492

○ WHE00108-201 WHITE	● WHE00108-202 YELLOW	● WHE00108-203 ORANGE
● WHE00108-204 RED	● WHE00108-208 BLUE	● WHE00108-209 ANTHRACITE
● WHE00108-210 BLACK	● WHE00108-214 PINK	



TEMPERATURE OF USE
-20°C / +35°C



SIZE
Universal-adjustable
from 51 to 62 cm



WEIGHT
420 g



CATEGORY
II

TECHNOLOGIES



UP & DOWN SYSTEM
A size adjustment system comprised of three components for all-day comfort. A central dial allows easy size adjustments, and side wings ensure a snug fit against the back of the head. The patented Up & Down hinge with helmet stability technology adapts as the wearer moves to deliver a more secure and personalized fit.



ANTI-INTRUSION MESH
Metal mesh vent covers that prevent debris from entering the ventilation channels while maintaining breathability.



2DRY LINER
A quick-drying fabric with moisture-wicking technology that accelerates the dispersion of sweat to the surface of the helmet padding for a drier, more comfortable wear.



VENTILATION CHANNELS
Designed with 10 air intakes and internal channels for enhanced breathability and wearer comfort.



RING TO HOOK
Chinstrap loop that enables the wearer to securely attach the helmet to a harness or other items.



VISOR ATTACHMENT POINTS
Helmet designed with attachment points for securing KASK eye protection accessories.



EARMUFF ADAPTER ATTACHMENT POINTS
Helmet designed with attachment points for earmuff adapters.



INTEGRATED LAMP CLIPS
Designed with 4 built-in, nylon lamp attachment points. Compatible with KASK headlamps and other headlamps with elastic bands.

PERFORMANCES

Protection against top impacts	K	5 kg from 2 m 100 J	Chinstrap release	K	>50 kg
Protection against side, front and rear impacts	K	5 kg from 0,5 m 25 J	Retention system effectiveness	K	
Protection against the penetration of objects	K	3 kg from 1 m 30 J			

K EN 12492 standard requirements

ADDITIONAL INFORMATION

3 YEARS
GUARANTEE

10 YEARS
SHELF LIFE

SHELF LIFE

10 years starting from the date of manufacture. The helmet must be checked regularly and before each use to detect the presence of any damage such as cracks, detachments, deformities, or peeling that represent factual elements of the state of deterioration of the helmet. Helmets that have suffered a severe impact shall be replaced even if they do not show obvious signs of damage.

GUARANTEE

3 years starting from the date of purchase.

CLEANING

Clean the helmet with the KASK Helmet cleaner or with water, neutral pH soap and a soft, clean cloth. The inner lining should be washed by hand in cold water or in the washing machine (max 30°C - 85°F). The KASK Liner Refresher is available to neutralise unpleasant odours.

STORAGE

The helmet should be stored away from direct sunlight or source of heat. We recommend the use of the KASK drawstring helmet bag to protect the helmet when not in use.

ADHESIVE APPLICATION

Do not apply adhesives, stickers or use paint and solvents on the helmet that do not comply with the manufacturer's specifications. Any alteration or intervention may impair its protective function.

SAFETY ACCESSORIES



WV100018
VISOR V2 PLUS



WV100024
FACE SHIELD



WV100003
VISOR FULL FACE



WV100006
MESH VISOR



WHP00004/5/6
EARMUFFS



WLA00001/2/3
HEADLAMPS



WPA00007
WINTER CAP



WAC00020/24
NECK SHADE



WAC00032/33
NECK SHIELD RW



WAC00036/37
SUN SHIELD

DISCOVER MORE



SCAN FOR
COMPLETE
COLLECTION