



WHF00111





MATERIAL

EXTERNAL SHELL: HD Polypropylene

INTERNAL SHELL: HD Expanded Polystyrene

HEADBAND: Soft PA Nylon



SIZE

Universal-adjustable from 52 to 63 cm



WEIGHT

460 g



STANDARD

EN 397 EN 50365 (Class 0) ★ Protection against top, front, rear and side impacts in conformity with EN 12492 Clauses 4.2.1 shock energy absorption capacity Clause 4.2.2 penetration EN 397 additional tests:



TEMPERATURE OF USE

440V a.c. / -30°C / LD / MM

-30°C / +50°C



WHE00111-201 WHITE	WHE00111-205 GREEN
WHE00111-202	WHE00111-208
YELLOW	BLUE
WHE00111-203	● WHE00111-210
ORANGE	BLACK
WHE00111-204 RED	



CATEGORY

TECHNOLOGIES



POLYPROPILENE HD EXTERNAL SHELL

Lightweight external shell with exponential better performance. Excels in impact absorption, especially at lower temperatures (-30°C). Resists yellowing and degradation.



HD EPS INTERNAL SHELL

Inner shell composed of high- density foam for all-around impact energy absorption and improved comfort.



CLICK-IN SYSTEM

Enhanced padding attachment system that quickly secures into place and allows for easy replacement, and removal. Patented system improves padding durability.



2DRY LINER

A quick-drying fabric with moisture-wicking technology that accelerates the dispersion of sweat to the surface of the helmet padding for a drier, more comfortable wear.



ERGO FIT SYSTEM

Helmet size adjusting system that allows for an easy and secure fit by turning the large diameter dial. The system moves up and down to adapt to a range of head shapes. The ergonomically shaped wings cradle the back of the neck for added comfort.



ELECTRIC SHOCK PROTECTION

Closed external shell protects against electrical hazards. Class E rated for work in electrical environments up to 20,000 volts.



ADVANCED LITE CHINSTRAP

Acrylic chinstrap with 5 adjustment points for a personalized fit. Accommodates wider head sizes and adapts to earmuff use. Color-coded fasteners indicate EN standard compliance rating.



RING TO HOOK

Chinstrap loop that enables the wearer to securely attach the helmet to a harness or other items.



LATERAL ADJUSTMENT DIVIDER

Side regulator point on chinstrap for adjustment and positioning for a more tailored fit.



EARMUFF ATTACHMENT SLOT

Helmet designed with standard 30 mm EURO slots for attaching KASK hearing protection earmuffs.



EARPLUG HOOKS

Lamp clip feature that holds corded earplugs.



FRONTAL ATTACHMENT POINT

Front attachment point for advanced customization and easy integration of accessories such as badge holders and headlamps. Includes cap cover for debris protection.



REPLACEABLE LAMP CLIPS

Helmet designed with 4 removable nylon lamp attachment clips. Compatible with KASK headlamps and other headlamps with elastic bands.



NECK PROTECTION SLOTS

3 rear helmet slots for mounting KASK Neck Protection accessories.



Helmet designed with integrated slots for easy mounting of KASK eye and face protection accessories. Easy Click Adapters required.













PERFORMANCES

Protection against top impacts	K	5 kg from 1 m 50 J
Protection against side, front and rear impacts	К*	5 kg from 0,5 m 25 J
Protection against top impacts	К*	5 kg from 2 m 100 J
Protection against the penetration of objects	K	3 kg from 1 m 30 J
Chinstrap release	K	>15 kg <25 kg

	1/	
Protection against electric shock		440V
Lower temperature resistance test	K	T= -30°C
Protection against side deformation	K	LD
Protection against molten metal splashes	K	MM

K EN 397 standard requirements

K[★] Additional compliance in conformity with the requirements of EN 12492

K EN 397 additional requirements

ADDITIONAL INFORMATION

SHELF LIFE

10 years starting from the date of manufacture. The helmet must be checked regularly and before each use to detect the presence of any damage such as cracks, detachment, deformities, or peeling that represents factual elements of the state of deterioration of the helmet. Helmets that have suffered a severe impact shall be replaced even if they do not show obvious signs of damage

3 years starting from the date of purchase

Clean the helmet with the KASK Helmet Cleaner or with water, natural pH soap and a soft, clean cloth. The inner lining should be washed by hand in cold water or in the washing machine (max 30°C - 85°F). The KASK Liner Refresher is available to neutralise unpleasant odours.

The helmet should be stored away from direct sunlight or source of heat. We recommend the use of KASK drawstring helmet bag to protect the helmet when not in use.

ADHESIVE APPLICATION

Do not apply adhesives, stickers or use paint and solvents on the helmet that do not comply with the manufacturer's specifications. Any alteration or intervention may impair its protective function.

SAFETY ACCESSORIES











DISCOVER MORE



WLA00001/2/3 HEADLAMPS











SCAN FOR COMPLETE COLLECTION

© 2023 KASK SPA. All rights resen

KASK S.p.A. / Via Firenze, 5 - 24060 Chiuduno (BG) - Italy T. +39 035 4427497 / F. +39 035 4427704 / info@kask.com









