HP VISOR CE

ΚΛ/Κ

FN

WHE00046





TECHNICAL DETAILS



MATERIAL EXTERNAL SHELL: ABS

INTERNAL SHELL: HD Polystyrene

HEADBAND: Soft PA Nylon



SIZE Universal-adjustable from 51 to 63 cm



WEIGHT 480 g (helmet)



STANDARD EN 14052

Protection against front, rear and side impacts in conformity with EN 12492 Clauses 4.2.1.2, 4.2.1.3, 4.2.1.4 shock energy absorption capacity Protection from impacts and penetration in conformitity , with EN 397 Clause 5.1.1 Shock Absorption Clause 5.1.2 Penetration Resistance

EN 397 ADDITIONAL TESTS: LD











TECHNOLOGIES

2DRY



A quick-drying technical fabric that accelerates the dispersion of sweat and moisture to the surface of the helmet padding for a drier, more comfortable wear.



MICROMETRICAL ADJUSTMENT

The micrometrical size regulation system positioned at the rear of the helmet provides quick and precise adjustment, even when wearing gloves.



EARMUFF ATTACHMENT SLOTS

Attachment points enable mounting earmuffs to helmet through bayonet adaptors.



HI-VIZ REFLECTIVE DECALS

Helmet designed with high visibility reflective adhesives for added safety in low visibility conditions.



INTEGRATED LAMP CLIPS

Designed with four built-in, nylon lamp attachment points. treatment.



VENTILATION CHANNELS

Ten air intakes that enhance breathability and comfort.



(f)

VISOR ATTACHMENT POINTS

Attachment points enable screw fastening of visor to helmet.

HP VISOR CE

ΚΛ/Κ

FN

PERFORMANCES

Protection against top impacts	К	5 kg from 2 m 100 J
Protection against side, front and rear impacts	K	5 kg from 1 m 50 J
Protection against the penetration of objects	K	3 kg from 1 m 30 J

Chinstrap release	K	>15 kg <25 kg
Retention system effectiveness	K	
Protection against side deformation	K**	

K** Additional tests performed to meet optional requirements

K Required performance tests

ADDITIONAL INFORMATION

GUARANTEE

3 years starting from the date of purchase.

SHELF LIFE

10 years starting from the date of manufacture. The helmet must be checked regularly and before each use to detect the presence of any damage such as cracks, detachments, deformities, or peeling that represent factual elements of the state of deterioration of the helmet. Helmets that have suffered a severe impact shall be replaced even if they do not show obvious signs of damage.

CLEANING

Clean the helmet with the KASK Helmet cleaner or with water, neutral pH soap and a soft, clean cloth. The inner lining should be washed by hand in cold water or in the washing machine (max 30°C - 85°F). The KASK Liner Refresher is available to neutralise unpleasant odours.

STORAGE

The helmet should be stored away from direct sunlight or source of heat. We recommend the use of the KASK drawstring helmet bag to protect the helmet when not in use.

ADHESIVE APPLICATION

Do not apply adhesives, stickers or use paint and solvents on the helmet that do not comply with the manufacturer's specifications. Any alteration or intervention may impair its protective function.

SAFETY ACCESSORIES



WVI00018 VISOR V2 PLUS



WLA00001/2/3 HEADLAMPS

WVI00024 FACE SHIELD



WVI00003 VISOR FULL FACE



WAC00020/24 NECK SHADE



WVI00006 MESH VISOR



WAC00032/33 NECK SHIELD RW

(f)



WHP00004/5/6 EARMUFFS













3

YEARS

WPA00007 WINTER CAP